

ALPEX

DAY & NIGHT VISION SCOPE



**Alpex Lite Kit
HO-M4-IR

**TH6K upgrade
available for \$50

Born for Low Light

The HIKMICRO ALPEX with advanced sensor technology and image processing to deliver a detailed, full colour image throughout the day automatically adjusting to twilight and continuing to display an amazing full colour image up until total darkness.

MODEL	RANGE	FOV	MAGNIFICATION	CMOS RESOLUTION	RRP
A50PL KIT	1500m	7.2° × 4.0°	4 - 24	4512 × 2512	\$2,249
A50PL					\$1,899
A50P KIT					\$1,949
A50P					\$1,599
A50EL KIT	1000m	8.8° × 5°	3.5 - 28	3840 × 2160	\$1,849
A50EL					\$1,499
A50E KIT					\$1,599
A50E					\$1,249
A40EL KIT	800m	10.7° × 6.1°	3.5 - 20.5	3840 × 2160	\$1,295
A40EL					\$ 999
A40E KIT					\$1,195
A40E					\$ 799



HIKMICRO

See the World in a New Way



PANTHER 2.0

THERMAL SCOPE



Compact yet Powerful

High thermal sensitivity, perfect detail recognition. Every detail matters when identifying targets. Less than 20 mK NETD helps identify small details of objects from their background easily and clearly even in the hardest weather and low-light conditions

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
PQ50L 2.0	2600m	8.8° × 5°	2.6	640 × 512, 12 μm NETD < 20mK	\$6,299
PQ35L 2.0	2600m	12.5° × 10°	1.82		\$5,299
PH50L 2.0	2600m	5.2° × 3.9°	4.33	384 × 288, 12 μm NETD < 20mK	\$4,799
PH35L 2.0	1800m	7.5° × 5.6°	3.03		\$4,299

**Ballistic Calculator features on all LRF Models

T16

TRAIL CAMERA



Powerful & Robust

The HIKMICRO T16 cameras are powerful and robust 4G-equipped cameras ideal for wildlife observation and extremely useful devices for hunting and a variety of other outdoor activities.

MODEL	RANGE	FEATURE	RESOLUTION	RRP
T16	25m Identification Range	0.4 Second Trigger Speed	Video 1080P Image 24MP	\$349
T16 Twin Pack	2x T16 Trail Cameras			\$659
T16 Single Bundle	1x T16 + SP5000			\$499
SP5000	SOLAR PANEL-Powerbank			\$179

** Available in AA or 18650 Battery Options

STELLAR 3.0

THERMAL TUBE SCOPE

Traditional tube with powerful performance.

The Stellar 3.0 Thermal Scopes feature high-resolution detectors (up to 1280 × 1024), 2560 × 2560 OLED displays, and NETD<15 mK sensitivity. With up to 3100 m detection range, built-in laser rangefinder, ballistic calculation, and 10-hour battery life, they offer precision and reliability for field and forest hunting.



STELLAR 3.0

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP	
SX60LS 3.0	3100m	14.6° × 11.7°	2.5-28.5	1280 × 1024, 12 μm NETD < 15mK	\$10,299	
SQ50L 3.0	2600m	8.8° × 7°	3.6-26.6	640 × 512, 12 μm NETD < 15mK	\$6,499	
SQ35L 3.0	1800m	12.5° × 10°	2.5-24.5		\$5,799	
SH50L 3.0	2600m	5.3° × 4°	6-24	384 × 288, 12 μm NETD < 15mK	\$4,799	
SH35L 3.0	1800m	7.5° × 5.7°	4.2-24.2		\$3,999	
SH35 3.0					\$3,499	

NEOS

THERMAL TUBE SCOPE

Precision Without Pause

HIKMICRO NEOS Thermal Scope is equipped with shutterless technology and the latest Sync Pro algorithm, ensuring excellent targeting accuracy even in challenging moments. With its compact and lightweight design, NEOS also brings great portability especially during long-time hunting.



MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
NH35L	1800m	7.6° × 5.7°	3.2× - 25.6×	384×288, 12 μm NETD < 18mK	\$2,999
NH25L	1200m	7.0° × 5.3°	3.5× - 24.5×	320×240, 12 μm NETD < 18mK	\$1,999
NE25	1200m	7.0° × 5.3°	3.5× - 24.5×	256×192, 12 μm NETD < 18mK	\$1,599

AU Office Email: australia@huntsmanoptics.com | orders@huntsmanoptics.com
AU Office Number: 02 4014 8200



HUNTSMAN
OPTICS

www.huntsmanoptics.com

DEFINE

HOW YOU SEE THE GAME



HABROK

MULTI-SPECTRUM BINOCULARS



*All Habrok range also available in a 940nm option

Enhanced Resolution

The Habrok Pro & 4K models combine thermal and digital optical channels, enhancing outdoor experiences. Compact like traditional binoculars but packed with advanced tech. Detect in thermal, view in optical, and record to built-in memory.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
HX60LS 4K	3100m / 400m	D 7.3° × 4.1° T 14.6° × 8.8°	D 5.5-22 T 2.6-20	1280 × 1024, 12µm NETD < 18mK	\$10,299
HQ50L 4K	2600m / 400m	D 7.3° × 4.1° T 8.8° × 5.3°	D 5.5-22 T 3.6-26.6	640 × 512, 12µm NETD < 15mK	\$6,499
HQ35L 4K	1800m / 400m	D 7.3° × 4.1° T 12.5° × 10.1°	D 5.5-22 T 3-22	640 × 512, 12 µm NETD < 20mK	\$5,799
HH35L 2.0 4K	1800m / 400m	D 7.3° × 4.1° T 7.5° × 5.6°	D 5.5-22 T 4.0-22	384 × 288, 12 µm NETD < 15mK	\$3,499
HE25L 2.0 4K	1200m / 400m	D 7.3° × 4.1° T 7° × 5.3°	D 5.5-22 T 4.3-17.2	256 x 192, 12µm NETD < 18mK	\$2,799

HABROK Pro & 4K

LYNX 3.0 & LYNX S

THERMAL MONOCULAR



*NETD < 15mK

Lightweight & Compact

Compact and light with a very comfortable and robust feel to it, the LYNX Monocular has the ultimate thermal performance housed in a small package. With advanced engineering, the refresh rate is smooth and fast – eliminating the need for recalibration as you scan your hunting zone.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
LQ35L 3.0	1800m	12.5°×7.5°	1.9 - 15.2	640×512, 12µm, NETD < 15mK	\$3,799
LQ35 3.0					\$3,299
LH35 3.0	1800m	7.5° × 4.6°	3.4-27.2	384× 288, 12 µm NETD < 15mK	\$2,399
LH25 3.0	1200m	10.5° × 6.4°	2.5-20		\$2,099
LH19 3.0	900m	13.8° × 8.4°	1.9-15.2	320×240, 12 µm NETD < 18mK	\$1,899
LH15 3.0	750m	11.7° × 8.8°	2.2-17.6		\$1,699
LE15 3.0	750m	11.7° × 8.8°	2.2-17.6	256 × 192, 12 µm NETD < 20mK	\$999
LE10 3.0	500m	18.0° × 13.6°	1.4-11.2		\$699
LC06 S	250m	24.7° × 18.7°	1.0- 4.0	160 × 120, 17µm*	\$579

LYNX 3.0 & S

FALCON

THERMAL MONOCULAR



Industry Leading Thermal Performance

The Falcon thermal monocular combines an advanced NETD<15 mK sensor with an F0.9 lens, ensuring exceptional imaging even in tough weather. The Falcon boasts a durable design, intuitive controls, and a 5-hour battery. Unique "Image Pro mode" enhances detail, supported by 64GB internal storage.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
FQ50L 2.0	2600m	8.8° × 7°	2.7-21.6	640 × 512, 12 µm NETD < 15mK	\$4,999
FQ50 2.0					\$4,299
FQ35 2.0	1800m	12.5° × 10°	1.9-15.2	640 × 512, 12 µm NETD < 20mK	\$3,699
FQ25	1200m	17.5° × 14°	1.4-11.2		\$3,199
FH35	1800m	7.5° × 5.7°	3-24	384 × 288, 12 µm NETD < 20mK	\$2,599
FH25	1200m	10.5° × 7.9°	2.2 – 17.6		\$2,299

FALCON

CONDOR

THERMAL MONOCULAR



Remarkable image quality

This compact spotter is equipped with a powerful, high-sensitivity NETD<15 mK thermal detector, which captures exceptionally fine detail. The result is a vivid, layered image, which doesn't just make it easy to spot and identify target quarry but also gives a very clear view of the surrounding landscape.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
CQ50L 2.0	2600m	8.7° × 7°	2.7 - 21.6	640 × 512, 12 µm NETD < 15mK	\$4,699
CQ35L 2.0	1800m	12.5° × 10°	1.9 - 15.2		\$4,099
CH35L	1800m	7.5° × 5.6°	3.5 - 28	384 × 288, 12 µm NETD < 20mK	\$2,999
CH25L	1200m	10.5° × 7.9°	2.5 - 20		\$2,699

CONDOR

THUNDER 2.0

THERMAL SCOPE



Impressive Detail Recognition

With an extremely high thermal sensitivity (NETD<20mK) detector combining a powerful thermal camera of up to 640x512 @12µm @ F1.0, it ensures informative images and an enhanced identification capability even under the slightest temperature differences.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
TQ50 2.0	2600m	8.8° × 7°	2.6 - 20.8	640 × 512, 12 µm NETD < 20mK	\$5,999
TQ35 2.0	1800m	12.5° × 10°	1.8 - 14.6		\$4,999
TH35P 2.0		7.5° × 5.7°	3 - 24	384 × 288, 12 µm NETD < 20mK	\$3,999
TH25P 2.0	1200m	10.5° × 7.9°	2.2 - 17.6		\$3,399
TE25 2.0		7° × 5.3°	3.3 - 26	256 × 192, 12µm NETD < 35mK	\$1,599
TE19 2.0	1000m	9.2° × 6.9°	2.5 - 19.8		\$1,499

THUNDER 2.0

THUNDER ZOOM 2.0

THERMAL SCOPE



Dual FOV Technology

With a 2.2x to 34.6x large magnification realized by the 384 detector @20mK, TH50Z 2.0 is the perfect match for both wooded and open field areas. A F0.8 large aperture also strengthens your viewing ability of objects.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
TQ60Z 2.0	1800m/ 3000m	12.5° × 10°/ 7.3° × 5.9°	1.8-14.6/ 3.1 - 25	640 × 512, 12 µm NETD < 20mK	\$6,999
TH50Z 2.0	1200m/ 2600m	10.5° × 7.9°/ 5.3° × 4°	2.2 - 17.4 / 4.3 - 34.6	384 × 288, 12 µm NETD < 20mK	\$4,999

THUNDER ZOOM 2.0

THUNDER 3.0

THERMAL CLIP-ON



*Fixed at base magnification in clip-on mode

Clip-On Versatility

These thermal clip-on boast high-resolution detectors @ 640 × 512, 1920 × 1080 OLED displays, and NETD < 15 mK sensitivity, offering detection ranges up to 2600m. With a 6-hour battery life and 1000 g shock resistance, they deliver top-tier performance in any environment.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
TQ50CL 3.0	2600m	8.8° × 7°	×1*	640 × 512, 12 µm NETD < 15mK	\$5,499
TQ50C 3.0	2600m	8.8° × 7°	×1*		\$5,199
TQ35CL 3.0	1800m	12.5° × 8°	×1*		\$4,999
TQ35C 3.0	1800m	12.5° × 8°	×1*		\$4,599
TH35C 3.0	1800m	7.5° × 5.7°	×1*	384 × 288, 12 µm NETD < 15mK	\$3,499

THUNDER 3.0

HIKTac

THERMAL SIGHT



See More, Track Fast

The HIKTac is designed for outdoor field applications, offering sharp thermal detection in low-light and challenging visual conditions. With high thermal sensitivity and a smooth 50Hz refresh rate, it helps users spot and track objects quickly and clearly. The large AMOLED display & optional laser range finder provide an immersive viewing.

MODEL	RANGE	FOV	MAGNIFICATION	SENSOR	RRP
TC19L	900m	9.2° × 6.9°	1.2 - 9.6	256 × 192, 12 µm NETD < 18mK	\$1,499

HIKTAC

A7E

ACTION CAMERA



Your Personal Shooting Coach

The HIKMICRO A7E is designed for hunters, clay shooters and sportsmen who want to capture every shot in sharp 4K detail. Compact and lightweight, it features up to 8x magnification, recoil-activated recording, long battery life and rugged IP67 protection for tough outdoor use.

MODEL	MAX RECOIL	STORAGE	MAGNIFICATION	VIDEO RESOLUTION	RRP
A7E	375g/1.7ms	64 GB Built-In	2 - 8	4K @60fps 2.7K @120fps 1080p @ 120fps 720p @120fps	\$699

A7E